

MODEL NUMBER	KEY	CFP-20T
Tons of force (maximum)		20
Approach speed (inches per minute)		186
Press speed (inches per minute)		44
Return speed (inches per minute)		269
Table (left to right)	A	21
Table (front to back)	B	16
U-Slot width	C	4
Daylight	D	18
Maximum stroke (adjustable)	E	12
Throat	F	11
Floor to table	G	36
Front to back	H	46
Height (overall)	I	88
Width	J	24
Clearance	K	6
Upper platen (left to right)	L	21
Upper platen (front to back)	M	16
Motor HP @ 1750 RPM		5 HP
Voltages available		230 / 460 / 575 3 PH. 60 HZ.

C FRAME PRESS 20 TON

STANDARD FEATURES

- ✓ Pressure gauge.
- ✓ Pressure regulator.
- ✓ Adjustable stroke control.
- ✓ Distance reversal switch.
- ✓ Pressure reversal switch.
- ✓ Indexable speed control.
- ✓ Ram travel is guided by 4 precision-ground rods (chromed).
- ✓ Jog mode used for simplifying setups.
- ✓ Dual Control - your choice of using:
 - (1) Moveable pedestal c/w dual electric palm buttons & extra emergency stop or
 - (2) Foot pedal.
- ✓ P.C.S. programmable control system.
- ✓ Quality BALDOR motor, low speed.
- ✓ Air-Cooled industrial oil cooler.

